CARE INSTRUCTIONS FOR MELAWOOD SUPAGLOSS

Minor scratches and scuffs can be removed by hand with selected automotive liquid, polishes and soft microfibre cloths. The polish must be suitable for painted surfaces.

ALWAYS ADHERE TO THE SUPPLIER'S INSTRUCTIONS.
Test the polish on an inconspicuous area first to ensure suitability.

Daily Cleaning

- Use a damp, soft, lint-free cloth.
- To remove grime, use a mild soap and water solution.
- Always prevent any moisture from penetrating any unprotected or exposed edges.
- Do not wipe surface with a dry cloth. This could lead to micro-scratching and will eventually dull the surface.
- Diluted window cleaning products are great for removing drying marks and smears on surfaces. (1 part window cleaner to 2 parts of water)

Do not use...

- Acetone
- Methyl Alcohol/MEK
- Amyl-acetate
- Butyl acetone
- Caustic Soda
- Chlorinated solvents
- Cresols/Phenols
- Ethyl-acetate
- Halogenated solvents
- Xylene
- Detergents with strong acids
- Power scouring pads and steel wool
- Abrasive compounds like washing powder, furniture cleaner and bleach.

- Thinners
- Ammonia
- Benzene
- Butyl alcohol
- Cellusolve
- Chloroform
- Dichloromethane
- Glacial acetate acid
- Toluene
- Steam cleaning equipment
- Solvents

